





Automatic tyre changer for racing competition and motorsport cars

Automatic tyre changer for race tyres with rim from 13" to 19" (max. wheel diameter 640mm/25", max. wheel width 330mm./13").



Main Features



Sport Dedicated to race car tyres



13"-19"

Allows to operate with tyre assemblies from 13" to 19".



Racing Tyre changer with reinforced chassis.



Quick Clamping

Rim clamping is performed by faceplate, cone and a quick ring nut (removes the restraint of the clamping range, normally found on conventional clamping chuck tyre changers).



Two speed chuck

Two speed hydraulic chuck, allows to adjust rotation speed in accordance with the type of operation to perform, ensures work efficiency and safety.



Move

The transportable machine can be positioned anywhere.

The information contained in this document is the sole property of Giuliano Suzhou The document is NOT authentic if it has been downloaded from a website different from www.giuliano.cn.







Description

Automatic tyre changer for race tyres with rim from 13" to 19" (max. wheel diameter 640mm/25", max. wheel width 330mm./13"). G1 Sport tyre changer is the result of Giuliano know-how, applied to race car tyres service, and it is uniquely dedicated to be used in most famous international motor sport events.

The tyre changer has been specially designed for tyre servicing in racing competitions, where performance, speed, and power are key factors for winners.

G1 Sport is approved & endorsed by the best race tyre manufacturers. Functions

- Pneumatic wheel clamping through center shaft and quick ring nut with nylon cone, to avoid any damage to the rim;
- Nylon made, self-centering support face plate, to avoid any damage to the rim;
- Adjustable bead breaker rollers, air operated, to break the bead of 13" 19" race tyres;
- Top bead fitting device all in one tool, including bead depressor;
- Equipped with "Easy-Move" transportation kit;
- Double rotation speed, 8 16 rpm;
- All mount and demount tools coated in nylon, in order to avoid any damage to the rim;
- "Easy Access" extractable pedal box for quick service.

Standard Features

Max. tyre diameter	640 mm (25")
Max. tyre width	330 mm (13")
Operating pressure	10 bar (145 psi)
Power supply	230V (1ph) 50÷60Hz
Motor power	0,75 kW
Rotating speed	8÷16 rpm
Net weight	195 Kg
Min overall dimensions	975 x 750 x 980 mm







Wheel clamping devices



2037399 Manual bead breaker

2037364 Manual bead depressor 2037611 Bead lifting lever









Scan QR code to go to product web page



Giuliano Automotive Equipment (Suzhou) CO.,Ltd

NO 8 Jinsheng Road SIP Suzhou (Jiangsu) P.R.China +86 0512 69368611 +86 0512 69367919 https://www.giuliano.cn



Giuliano Automotive Equipment (Suzhou) CO.,Ltd

The information contained in this document is the sole property of Giuliano Suzhou The document is NOT authentic if it has been downloaded from a website different from www.giuliano.cn.