



## Semiautomatic tyre changer with sideways moving arm

Semiautomatic tyre changer with sideways moving arm, expressly designed for oversize and racing tyres. It is suitable for car and motorcycle wheels having rim size from 10" to 22" (max. diameter 1200mm/47,5", max. wheel width 390 mm/15").

### Main Features



**Car**  
Suitable for car wheels



**Semiautomatic**  
Model with 3 control pedals, fixed vertical tower, swinging horizontal arm and operating arm with manual lowering and locking by hand-lever.



**10"-22"**  
Allows to operate with tyre assemblies from 10" to 22".



**Racing**  
Tyre changer with reinforced chassis.



**Jaw Clamping**  
Rim clamping is performed by means of 4 jaws facing each other, driven by pneumatic cylinders connected to the control pedal.



**Blade Bead Breaking**  
Bead breaking by conventional blade, works with tyre assembly in vertical position



## Description

Semiautomatic tyre changer with sideways moving arm, expressly designed for oversize and racing tyres. It is suitable for car and motorcycle wheels having rim size from 10" to 22" (max. diameter 1200mm/47,5", max. wheel width 390 mm/15").

### Features

- Fixed vertical arm-Sideways moving horizontal arm;
- Locking system by handwheel;
- 20" turntable, outside clamping;
- Air operated bead breaker;
- Oversize body;
- Motor 230/400V-3ph-50Hz.

## Standard Features

|   |                         |
|---|-------------------------|
| Rim clamping range                      | 10" - 24"               |
| Max. tyre diameter                      | 1200 mm (47,5")         |
| Max. tyre width                         | 390 mm (15")            |
| Max. bead-breaker cylinder force        | 24700 N                 |
| Operating pressure                      | 10 bar (145 psi)        |
| Power supply                            | 230/400 V 3ph           |
| Motor power                             | 0,55 kW                 |
| Max. spindle torque                     | 1200 Nm                 |
| Inflating pressure limiting device max. | 3,5 bar (50 psi)        |
| Net weight                              | 220 Kg STD<br>225 Kg GT |







Scan QR code to go to product web page



Giuliano Automotive Equipment (Suzhou) CO.,Ltd

NO 8 Jinsheng Road

SIP Suzhou (Jiangsu)

P.R.China

+86 0512 69368611

+86 0512 69367919

<https://www.giuliano.cn>

