



Semiautomatic tyre changer with sideways moving arm

Semiautomatic tyre changer with sideways moving arm, suitable for car and motorcycle wheels having rim size from 10" to 20" (max. diameter 1000mm/39", max. wheel width 330 mm/13").

Main Features



Car
Suitable for car wheels



Semiautomatic
Model with 3 control pedals, fixed vertical tower, swinging horizontal arm and operating arm with manual lowering and locking by hand-lever.



10"-20"
Allows to operate with tyre assemblies from 10" to 20".



Jaw Clamping
Rim clamping is performed by means of 4 jaws facing each other, driven by pneumatic cylinders connected to the control pedal.



Blade Bead Breaking
Bead breaking by conventional blade, works with tyre assembly in vertical position



Description

Semiautomatic tyre changer with sideways moving arm, suitable for car and motorcycle wheels having rim size from 10" to 20" (max. diameter 1000mm/39", max. wheel width 330 mm/13").

Features

- Fixed vertical arm;
- Sideways moving horizontal arm;
- Operating arm locking by handwheel ;
- 18" turntable, outside clamping ;
- Air operated bead-breaker;
- Extractable pedal unit;
- Oversize body
- Motor 230/400V-3ph-50Hz.

Standard Features

Rim clamping range	10" - 20"
Max. tyre diameter	1000 mm (39")
Max. tyre width	330 mm (13")
Max. bead-breaker cylinder force	2500 kg
Operating pressure	10 bar (145 psi)
Power supply	230/400 V 3ph
Motor power	0,55 kW
Max. spindle torque	1200 Nm
Inflating pressure limiting device max.	3,5 bar (50 psi)
Net weight	195 kg STD 213 kg GT



S 112 F
Standard Accessories





S 112 F
Optional Accessories





Scan QR code to go to product web page



[Giuliano Automotive Equipment \(Suzhou\) CO.,Ltd](#)

NO 8 Jinsheng Road

SIP Suzhou (Jiangsu)

P.R.China

+86 0512 69368611

+86 0512 69367919

<https://www.giuliano.cn>

