



Semi-automatic swing arm tyre fitting machine for motorcycles, scooters & ATV tyres

Semi-automatic swing arm tyre fitting machine for motorcycles, scooters & ATV tyres with rim from 6" to 24" (max. tyre diameter 1010 mm./39", max. tyre width 240mm./9,5").

Main Features



Bike
Suitable for motorcycle wheels



Semiautomatic
Model with 3 control pedals, fixed vertical tower, swinging horizontal arm and operating arm with manual lowering and locking by hand-lever.



6"-24"
Allows to operate with tyre assemblies from 6" to 24".



Jaw Clamping
Rim clamping is performed by means of 4 jaws facing each other, driven by pneumatic cylinders connected to the control pedal.



Blade Bead Breaking
Bead breaking by conventional blade, works with tyre assembly in vertical position



Description

Semi-automatic swing arm tyre fitting machine for motorcycles, scooters & ATV tyres with rims from 6" to 24" (max. wheel diameter 1010 mm./39", max. wheel width 240mm./9,5").

Functions

- Robust vertical tower, swinging horizontal arm with \varnothing 36 mm operating arm;
- Bead breaker double effect Cylinder \varnothing 200 mm;
- Reinforced Chassis;
- Tabletop thickness 12 mm, specially designed for motorcycle wheels;
- Fitting head designed for both standard and low profiled tyre applications;
- Plastic protections on fitting head to avoid any damage to alloy rim;
- Four motorcycle clamping jaws adjustable to 4 different positions: 6"-13", 10"-17", 14"-21", 17"-24";
- Two powerful clamping cylinders provide uniform clamping pressure;
- Tyre inflation by pedal (optional);
- Suitable for Press Arm Eco (optional).

Standard Features

Rim clamping range from outside	6" - 24"
Max. tyre diameter	1010 mm (39")
Max. tyre width	240 mm (9,5")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph 220V-1ph
Motor power	0,55 kW (3ph)
Rotating speed	7 rpm (3ph)
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	175 Kg
Max overall dimensions	1110 x 960 x 1710 mm



Standard accessories




QCBM (9238544)
Quick release kit for S116 Bike and S226 Bike shovel, including wider bead breaker shovel for bigger motorcycle tyre applications.



ATV-ADM (9215704)
Kit of 4 motorcycles adaptors with wider clamps, oversize height



MOTO-ADM (9215664)
Kit of 4 motorcycles adaptors with wider clamps, standard height.



SHIM (9215390)
Kit of 4 shims for wider clamps (only for MOTO-ADM and ATV-ADM)



QCKM (9218323)
Hex bar with quick release system for motorcycle wheels mounting tools.



SHSM (9215383)
Standard mounting tool with hub, for quick release kit (only in combination with QCKM).



PHSM (9215386)
Plastic mounting tool with hub, for quick release kit (only in combination with QCKM).



GHSM (9215385)
6"-12" mounting tool with hub, for quick release kit (only in combination with QCKM)



KHSM (9215387)
4" mounting tool with hub, for quick release kit (only in combination with QCKM).



PA ECO (9236722)
PRESS ARM ECO additional arm to ease mounting operations of low profiled and UHP tyres.



BAR-G (9298185)
CE inflating gauge



PSI-G (9299684)
Extra-CE inflating gauge.



PED-G (9236373)
Pedal operated inflating device.



HD (9208633)
Manual bead depressor.



PAD (9237711)
Manual bead depressor with extendable travelling pad.



CPC (9214251)
Pressing cone for clamping RUN FLAT tires from outside.



Scan QR code to go to product web page



Giuliano Automotive Equipment (Suzhou) CO.,Ltd

NO 8 Jinsheng Road

SIP Suzhou (Jiangsu)

P.R.China

+86 0512 69368611

+86 0512 69367919

<https://www.giuliano.cn>

