







Automatic Tilt Back Tyre Changing Machine for motorcycles, scooters & ATV Tyres

Automatic tilt back tyre changing machine for wheels with rim from 6" to 24" (max. wheel diameter 1100 mm./43", max. wheel width 240mm./9,5"). Suggested for motorcycle tyre specialists, servicing motorcycles, scooters and ATV tyres.

Main Features



5 226 Bike



Description

Automatic tilt back tyre changing machine for wheels with rim from 6" to 24" (max. wheel diameter 1100 mm./43", max. wheel width 240mm./9,5").

Functions

- Tilting tower, sliding horizontal arm with ø 41 mm operating arm;
- Bead breaker double effect Cylinder ø 200 mm;
- · Reinforced Chassis;
- Tabletop thickness 12 mm, specially designed for motorcycle wheels;
- Fitting head designed for both standard and low profiled tyre applications;
- Plastic protections on fitting head to avoid any damage to alloy rim;
- Four motorcycle clamping jaws adjustable to 4 different positions: 6"-13", 10"-17", 14"-21", 17"-24";
- Two powerful clamping cylinders provide uniform clamping pressure Tyre inflation by pedal (optional)
- Suitable for Press Arm Eco (optional);
 "Easy Access" extractable pedal box for quick service.

Standard Features

Rim clamping range from outside	6" - 24" Adjustable jaws can be pre-set in 3 different holes on slides, to start clamping range from 10", 11" or 12". Tabletop cylinder stroke = 10"
Max. tyre diameter	1100 mm (43")
Max. tyre width	240 mm (9,5")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph / 220V - 1ph
Motor power	0,55 kW (3ph)
Rotating speed	7 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	225 Kg
Max overall dimensions	1170 x 1820 x 1910 mm



5 226 BikeStandard Accessories



TICO

Standard accessories



5 226 BikeOptional Accessories





QCBM (9238544)

Quick release kit for S116 Bike and S226 Bike shovel, including wider bead breaker shovel for bigger motorcycle tyre applications.



ATV-ADM (9215704)

Kit of 4 motorcycles adaptors with wider clamps, oversize height



MOTO-ADM (9215664)

Kit of 4 motorcycles adaptors with wider clamps, standard height.



SHIM (9215390)

Kit of 4 shims for wider clamps (only for MOTO-ADM and ATV-ADM)



QCKM (9218323)

Hex bar with quick release system for motorcycle wheels mounting tools.



SHSM (9215383)

Standard mounting tool with hub, for quick release kit (only in combination with QCKM).



PHSM (9215386)

Plastic mounting tool with hub, for quick release kit (only in combination with QCKM).



GHSM (9215385)

6"-12" mounting tool with hub, for quick release kit (only in combination with QCKM)



KHSM (9215387)

4" mounting tool with hub, for quick release kit (only in combination with QCKM).



PA ECO (9236722)

PRESS ARM ECO additional arm to ease mounting operations of low profiled and UHP tyres.



BAR-G (9298185) CE inflating gauge



PSI-G (9299684)

Extra-CE inflating gauge.



PED-G (9236373)

Pedal operated inflating device.



HD (9208633)

Manual bead depressor.



PAD (9237711)

Manual bead depressor with extendable travelling







Scan QR code to go to product web page



Giuliano Automotive Equipment (Suzhou) CO.,Ltd

NO 8 Jinsheng Road SIP Suzhou (Jiangsu) P.R.China

+86 0512 69368611

+86 0512 69367919

https://www.giuliano.cn

