



Truck tyre changer 14"-26"

Tyre changer suitable for truck and bus fleets (for both tube and tubeless tyres) with 14" - 26" rim (max. wheel diameter 1200 mm./47"; max. wheel width 780 mm./30").

Main Features



Truck
Suitable for truck wheels



14"-26"
Allows to operate with tyre assemblies from 14" to 26".



Quick Clamping
Rim clamping is performed by faceplate, cone and a quick ring nut (removes the restraint of the clamping range, normally found on conventional clamping chuck tyre changers).



Joystick
Allows to move the tool with maximum simplicity and accuracy.



Roller Bead Breaking
Bead breaking by disks, without contact with the rim, works with tyre assembly in horizontal position



Description

Tyre changer suitable for truck and bus fleets with 14" - 26" rim (max. wheel diameter 1200 mm./47"; max. wheel width 780 mm./30"). Equipped with manual wheel clamping system by faceplate, cones and ring nut; also equipped with traditional double tool for mounting/removing tubeless and/or tube tyres.

Functions

- Hydraulic movement of clamping chuck holding arm (up-down);
- Hydraulic travel movement of operating arm carriage (left-right);
- Operating arm manual tilting;
- Double tool (disk + finger) manual rotation;
- Wheel clamping by face plate, cones and ring nut;
- Operating arm and clamping chuck arm facing each other;
- All motions controlled by joysticks;
- Safety switches and electric circuit breakers for both pump motor and chuck motor.

Standard Features

Rim clamping range	14" - 26"
Max. tyre diameter	1200 mm (47")
Max. tyre width	780 mm (30")
Bead breaker force	18300 N
Operating pressure	130 bar (1885 psi)
Power supply	400V / 230V - 3ph (50 Hz)
Hydraulic pump motor power	1,1 kW (3 ph)
Clamping chuck motor power	1,1 kW (3 ph)
Net weight	400 kg
Max. tyre assembly weight	1500 kg
Max overall dimensions	1330x1570x1500x1160 mm



Standard accessories





TBSR 2 (9218165)
Roller tool for mounting / demounting tubeless truck
tyres



AGC (9299271)
Clamp for alu-rims.



SGC (9236972)
Bead clamp with extra slide, for skidder tyre
applications.



WGC (9219656)
G-Clamp with wider bead-press angle, for agriculture
tyres.



Scan QR code to go to product web page



Giuliano Automotive Equipment (Suzhou) CO.,Ltd

NO 8 Jinsheng Road

SIP Suzhou (Jiangsu)

P.R.China

+86 0512 69368611

+86 0512 69367919

<https://www.giuliano.cn>

