



S 810



Digital electronic wheel-balancer with LED display

Digital electronic wheel-balancer with LED display.

Main Features



Fast & Easy Split

Fast & Easy Split (FES) divides the counterweight needed to correct imbalance, based on the installation position behind the spokes of the aluminium rim. Requires a very simple, very quick operation without the need to enter...



Car

Suitable for car wheels

Giuliano Automotive Equipment (Suzhou) CO.,Ltd

The information contained in this document is the sole property of Giuliano Suzhou The document is NOT authentic if it has been downloaded from a website different from www.giuliano.cn.



Description

The balancer is standard supplied with cones and quick clamping ring nut.
Functions

- Manual measuring of wheel diameter and distance;
- Automatic START and STOP;
- Static and dynamic balancing;
- Huge combination of ALU programs;
- Special ALU-S program;
- FES function;

Standard Features

Max. wheel weight	75 kg
Max. tyre diameter	900 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1.5"-20" / 40-510 mm
Power supply	230V - 1ph - 50/60 Hz
Cycle time	6s (5 3/4 "x 14") 15 Kg
Balancing speed	< 100 rpm
Balancing precision	± 1g
Net weight	90 kg



Standard accessories

Standard accessories

Standard accessories



UNILUG (9342855)
Wheel clamping adaptor for wheels without central hole or with special flanging



9342856
Kit of 5 quick-lock centering stud bolts for Unilug



9342860
Set of 5 extra-long spherical nuts for Unilug



9342861
Clamping cone with spacer for SUV and 4WD wheels; central hole diam. 122-174 mm



9342862
Clamping cone with spacer for clamping wheels of LCVs and vans; central hole diam. 198-225 mm



9342863
Special cone for clamping wheels from outside; central hole diam. 100-118 mm



9342867
Spacer kit for clamping SUV or 4WD all terrain wheels, to prevent the wheel from touching wheelbalancer baseframe.



QUICKPLATE (9342864)
Wheel clamping adaptor with flange and 4 centering stud bolts, for wheels with max. 4 lug holes



QUICKPLATE (9342865)
Wheel clamping adaptor with flange and 5 centering stud bolts, for wheels with max. 5 lug holes



QUICKPLATE (9342866)
Wheel clamping adaptor with flange and 6 centering stud bolts, for wheels with max. 6 lug holes



RL (9314901)
RL protective sleeve for alloy rims.




PRU 810 (9336589)
Wheel guard for S810



WBL81 (9437137)
WBL81 wheel lift, for wheel easy positioning and centering on the shaft, without any effort for the operator.



PROBIKE EKO KIT (9341191)
Clamping adaptor for motorcycle wheels. Complete with 14 mm diam. shaft. and Quick Fix quick clamping device



9342850
Set of 28 mm centering rings for ProBike Eco Kit with 14 mm diam. shaft



9342851
19 mm diam. shaft with complete set of centering rings, adaptors and Quick Fix quick clamping device, for ProBike Eco



PROFI KIT (9342852)
Set of special adaptors for 19 mm diam. shaft on ProBike Eco



9342853
10 mm diam. shaft with adaptors, for ProBike Eco



Scan QR code to go to product web page



[Giuliano Automotive Equipment \(Suzhou\) CO.,Ltd](#)

NO 8 Jinsheng Road

SIP Suzhou (Jiangsu)

P.R.China

+86 0512 69368611

+86 0512 69367919

<https://www.giuliano.cn>

